



Nylon Mesh Panel Filter

Description:

Nylon mesh panel filters also known as 'flyscreen' pre-filters can be manufactured to any size. The nylon mesh attracts and traps airborne particles such as dust, dirt, and pollen. Nylon mesh pre-filters are mainly used as a low-cost alternative to metallic pre-filters in air conditioning systems.

Application:

Suitable for most air-conditioning, ventilation, or exhaust applications. Can be used as a primary filter, suitable for acid base application.

Manufacture:

Frame: Aluminium frame

Media: Washable nylon mesh



PERFORMANCE DATA

<i>Class (EN779):</i>	G2-G3
<i>Average Arrestance (One Layer)</i>	72.5% - 90g/sq.ft – G2
<i>Average Arrestance (Two Layers)</i>	81.5% - 143g/sq.ft – G3
<i>Final Pressure Drop (Recommended)</i>	150Pa
<i>Maximum Pressure Drop</i>	250Pa
<i>Max Operating Temp</i>	250°C

Note: All information is correct to the knowledge of Advance Filtration Group Pty. Ltd. at the time of publication. No assurance is implied. Please confirm all Advance Filtration Group Pty. Ltd. products with a technical representative for the suitability of the Advance Filtration Group Pty. Ltd. product within your installation and location within Australia. © Copyright Advance Filtration Group Pty. Ltd 2020